



# HP Stitch S500 64-in Printer

The most efficient printer for highly demanding dye sub users<sup>1</sup>



## Color you can rely on with HP SmartColor

- Confidently distribute jobs across your fleet with best-in-class color consistency from printer to printer.<sup>1</sup>
- Get accurate colors over time, even as environmental conditions change, with the built-in spectrophotometer.
- Automatically detect when a color is out of gamut and get the closest visual match with PANTONE® emulation.<sup>2</sup>
- Easily create color profiles in half the time<sup>4</sup>, or use finished profiles from our cloud-based library.<sup>3</sup>

## Streamline your production

- Run at top speed while producing richly saturated color, with the symmetrical 2xCMYK printhead configuration.
- Print an entire shift unattended or overnight with the largest media rolls<sup>1</sup> and large ink supplies.
- Stay in control and maximize uptime with real-time fleet management and HP Smart Services.

## Reduce your costs and increase your efficiency

- Reduce your media costs and avoid cockling when using lightweight transfer paper with the Drop & Dry system.
- Avoid reprints and media waste with 1200 dpi printheads and the Smart Nozzle Compensation system.
- Save 50% floor space with the first dye-sub printer with front media loading.<sup>1</sup>

For more information, please visit <http://www.hp.com/go/stichs500>

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: <http://www.hp.com/go/learnaboutsupplies>

<sup>1</sup> Compared to alternative 64-inch dye-sublimation based textile printers available as of January, 2019. Only the HP Stitch S Printer series provides HP SmartColor tools and a built-in spectrophotometer for a better color management experience.

<sup>2</sup> Automatically detects when a PANTONE® color is out of gamut.

<sup>3</sup> Find a comprehensive list of all compatible media along with finished color profiles and printer settings at <http://www.hp.com/go/mediasolutionslocator>.

<sup>4</sup> Based on internal and third-party testing in January, 2019 evaluating the number of interactions and time required to create a typical color profile compared to leading 64-inch dye-sublimation based textile printers available as of January, 2019.

## Technical specifications

### Print

Printing modes	110 m <sup>2</sup> /hr - Max Speed (1-pass) 62 m <sup>2</sup> /hr - Production Fast (2-pass) 43 m <sup>2</sup> /hr - Production Quality (3-pass) 34 m <sup>2</sup> /hr - Quality (4-pass) 22 m <sup>2</sup> /hr - High Quality (6-pass) 1185 ft <sup>2</sup> /hr - Max Speed (1-pass) 665 ft <sup>2</sup> /hr - Production Fast (2-pass) 460 ft <sup>2</sup> /hr - Production Quality (3-pass) 365 ft <sup>2</sup> /hr - Quality (4-pass) 235 ft <sup>2</sup> /hr - High Quality (6-pass)
Print resolution	Up to 1200 x 1200 dpi
Ink types	HP Dye Sub Inks
Ink cartridges	4 (cyan, magenta, yellow, black)
Cartridge size	3 L
Printheads	8 HP Thermal Inkjet (4 cyan/black, 4 magenta/yellow)
Long-term print-to-print repeatability	Average <= 1 dE2000, 95% of colors <= 1.5 dE2000 <sup>1</sup>

### Media

Handling	Roll feed, take-up reel; automatic cutter (for transfer media)
Media types	Sublimation transfer papers, sublimation polyester fabrics, sublimation film
Roll size	580 to 1625-mm rolls (23 to 64-in rolls)
Roll weight	55 kg (121 lb)
Roll diameter	250 mm (9.8 in)
Thickness	Up to 0.5 mm (0.02 in)

**Applications** Interior decoration; Fashion; Sportswear; Soft signage

### Connectivity

Interfaces	Gigabit Ethernet (1000Base-T)
------------	-------------------------------

### Dimensions (w x d x h)

Printer	2560 x 710 x 1420 mm (101 x 28 x 56 in)
Shipping	2750 x 1053 x 1696 mm (108 x 42 x 67 in)
Operating area	

### Weight

Printer	226 kg (498 kg)
Shipping	355 kg (782 lb)

**What's in the box** HP Stitch S500 64-in Printer; printer stand; printheads; maintenance cartridge; ink collector; take-up reel; loading accessory; 2-in adaptor kit; beacon light; edge holders; user maintenance kit; quick reference guide; setup poster; documentation software; power cords

### Environmental ranges

Operating temperature	15 to 30°C (59 to 86°F)
Operating humidity	20 to 80% RH (non-condensing)

### Acoustics

Sound pressure	55 dB(A) (operating); 38 dB(A) (idle); < 16 dB(A) (sleep);
Sound power	7.3 B(A) (operating); 5.6 B(A) (idle); < 3.5 B(A) (sleep);

### Power

Consumption	1 kW (printing); 80 W (ready); < 2 W (sleep)
Requirements	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); one power cord; 13 A max

### Certification

Safety	IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Ukraine (UA); Argentina (IRAM)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC)
Environmental	ENERGY STAR®; WEEE; EU RoHS; China RoHS; RoHS Korea; RoHS India; RoHS Ukraine; RoHS Turkey; REACH; EPEAT Bronze; OSHA; CE marking compliant

**Warranty** One-year limited hardware warranty

## Ordering information

### Product

2ET73C	HP Stitch S500 64-in Printer
--------	------------------------------

### Accessories

5JX30A	HP Stitch S300/S500 Ink Collector
5Q659A	HP Ergosoft Pro RIP Color Edition
5Q672A	HP Stitch S300/S500 User Maintenance Kit
F0M64A	HP Latex 3x0 Edge Holders
T7U74A	HP Latex 300/500 Ink Collector

### Original HP printing supplies

2LL57A	HP 636 3-liter Black Stitch Dye Sublimation Ink Cartridge
2LL58A	HP 636 3-liter Cyan Stitch Dye Sublimation Ink Cartridge
2LL59A	HP 636 3-liter Magenta Stitch Dye Sublimation Ink Cartridge
2LL60A	HP 636 3-liter Yellow Stitch Dye Sublimation Ink Cartridge
2LL61A	HP 614 Stitch Dye Sublimation Printhead Cleaning Kit
2LL62A	HP 614 Cyan and Black Stitch Dye Sublimation Printhead
2LL63A	HP 614 Magenta and Yellow Stitch Dye Sublimation Printhead
2LL76A	HP 636B 3-liter Black Stitch Dye Sublimation Ink Cartridge
2LL77A	HP 636B 3-liter Cyan Stitch Dye Sublimation Ink Cartridge
2LL78A	HP 636B 3-liter Magenta Stitch Dye Sublimation Ink Cartridge
2LL79A	HP 636B 3-liter Yellow Stitch Dye Sublimation Ink Cartridge

### ECO highlights

- ECO PASSPORT certified dye sublimation inks<sup>1</sup>
- ENERGY STAR® certified<sup>2</sup>
- EPEAT® Bronze registered as environmentally preferable product<sup>3</sup>
- Free, convenient HP ink cartridge and printhead recycling<sup>4</sup>

Please recycle large-format printing hardware and printing supplies. Find out how at our website [hp.com/ecosolutions](http://hp.com/ecosolutions)

<sup>1</sup> Original HP Dye Sublimation Inks for the HP Stitch S Printer series are certified ECO PASSPORT by Oeko-Tex,® which is a globally uniform testing and certification system for textile chemicals, colorants, and auxiliaries. It consists of a two-step verification procedure that analyzes whether the compounds and each ingredient meet specific criteria for sustainability, safety, and regulatory compliance.

<sup>2</sup> ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

<sup>3</sup> EPEAT® registered where applicable. EPEAT registration varies by country. See <http://www.epeat.net> for registration status by country.

<sup>4</sup> Program availability varies. Please check <http://www.hp.com/recycle> for details.

<sup>1</sup> The color variation inside a printed job has been measured at 6-pass mode on transfer media and also in direct-to-fabric situations within this limit: maximum color difference (95% of colors) <= 1.5 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012, 5% of colors may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results. Results are dependent on sublimation process variability.

