

WALL COVERING

WALL COVERING



LATEX



UV



Certified for
HP Latex Inks

KAVALAN
GECKO 320GB



Gecko
320GB



Product
Carbon
Footprint

1.5 kg
CO₂ eq / sqm
Cradle to Grave

EXPLORE MORE WITH   

M MAX WIDTH

TEST METHOD: DIN EN ISO 2286-1

5m

T TENSILE STRENGTH (W/F)

TEST METHOD: DIN 53354

200/110 kg / 5cm

T TEMPERATURE RANGE

TEST METHOD: DIN 53361

-40~+90 °C

T TEAR RESISTANCE (W/F)

TEST METHOD: DIN 53363

20/9 kg

W WEIGHT

320±20 gsm

T THICKNESS

0.33±0.02 mm

R REGULAR ROLL LENGTH

50m

COATING

- Water-based
- Phthalate free

COMPOSITION

- Polyester yarn
- PVC-free coating

CHARACTERISTICS

- Lightweight
- Low shrinkage
- Perfect for high quality digital printing
- Waterproof and stainproof on print side

APPLICATIONS

- Interior wall decorations
- Ceiling coverings

FLAME RETARDANT STANDARDS

- DIN4102- B1
- EN13501- 1
- NFPA701